

Please insert the following subtitle on page 1,  
line 11:

PRIOR ART

Please insert the following subtitle on page 3,  
line 22:

OBJECT AND SUMMARY OF THE INVENTION

Please insert the following subtitle on page 6,  
line 15:

BRIEF DESCRIPTION OF THE DRAWINGS

Please insert the following subtitle on page 7,  
line 8:

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT(S) OF THE  
INVENTION

IN THE CLAIMS

Please cancel claims 1-6 without prejudice.

Please add the following new claims 7-15:

1. (New) A vehicle jack having a support leg  
(1), a foot (3) rotatably engaged on a pivot (6) on an end  
of the support leg (1) and a first end of a vehicle support  
arm (2) rotatably engaged on the support leg (1) above the  
foot (3) so that a threaded screw spindle (10) engaged to  
both the support leg (1) and the vehicle support arm (2) can

be rotated by a handle (19) to turn the vehicle support arm (2) relative to the support leg (1) and raise a vehicle support (4) engaged on a second end of the vehicle support arm (2), wherein an auxiliary support (23) acts against the foot (3) during the raising of the vehicle support both when unloaded and when unloaded;

wherein the auxiliary support (23) has a first section engaged to the first end of the vehicle support arm (2) and a second section engaged to the foot (3), the second section having an elbow-shaped projection (5) at a free end thereof;

a1 wherein the support leg (1) has a tongue (7) with a first hole (8) through which the first section of the auxiliary support (23) passes to permit the second section to engage the foot (3);

wherein the foot (3) has a leg (12) between the pivot (6) and the tongue (7) projecting up from a bottom of the foot (3) into a recess (21) in a lower end of the support leg (1) in which the free end of the second section of the auxiliary support (23) engages the leg (12).

2/8. (New) A vehicle jack, in accordance with claim 1, wherein the support leg (1) has a central elevation (22) above the tongue (7) having a second hole (15) into which the elbow-shaped projection (5) projects and moves and

a leg (10) projecting down from an edge of the second hole (15) engaged in a third hole (16) in the bottom of the foot.

3  
9. (New) A vehicle jack in accordance with claim 1, wherein the first section and the second section of the auxiliary support form an obtuse angle.

4  
10. (New) A vehicle jack in accordance with claim 1, wherein the auxiliary support runs through an interior of the support leg.

Q1 5  
11. (New) A vehicle jack in accordance with claim 1, wherein the lower end of the support leg is triangular.

6  
12. (New) A vehicle jack, in accordance with claim 1, wherein the auxiliary support (23) has a circular cross section.

7  
13. (New) A vehicle jack in accordance with claim 1, wherein the auxiliary support (23) has a rectangular cross section.

8  
14. (New) A vehicle jack, in accordance with claim 1, wherein the auxiliary support (23) is metallic.